



# 2294L 21.5-inch LCD

Open-Frame Touchscreen



Integrated Touch



Commercial Grade



3-Year Warranty

## Product Overview

The Elo 2294L 21.5-inch open-frame LCD touchscreen features a slim design and narrow outside dimensions due to the state-of-the-art, energy-saving LED backlight, using less electricity to operate and generating less heat. This compact display is designed for touch, with proven Elo expertise and reliability built in. The 2294L provides stable, drift-free operation with outstanding image clarity and light transmission for accurate touch responses and vivid images. Featuring a brilliant wide viewing angle panel, the open-frame touchscreen instantly grabs and holds the users' attention for kiosks, casino and amusement, retail self-service, and industrial automation environments.

**Choice of Elo touch technologies:**  
Standard bezel: IntelliTouch<sup>®</sup> SAW and IntelliTouch<sup>®</sup> Dual-Touch SAW  
Zero-bezel: TouchPro<sup>™</sup> PCAP

**Elo's TouchPro PCAP offers:**

- 2GS (two glass solution) with pristine optical clarity and touch durability.
- 10 touch with thru-glass capabilities that passes UL-60950 & IK-07 impact testing

**Video Interfaces: HDMI, VGA & Display Port**

## 2294L 21.5-inch Open-Frame Touchscreen

| Specifications              |  |
|-----------------------------|--|
| Model                       | 2294L  |
| Color                       | Black  |
| Active Display Area         | 18.76" x 10.55" / 476.64mm x 268.11mm  |
| Diagonal                    | 21.5"  |
| Aspect Ratio                | 16:9   |
| Dimensions                  | Bezel: 20.12" x 11.74" x 1.65" / 511.8mm x 298.2mm x 42mm<br>Zero-Bezel: 20.31" x 12.24" x 1.49" / 516mm x 311mm x 37.9mm  |
| Native Resolution           | 1920 x 1080 at 50, 60 Hz   |
| Other Supported Resolutions | 640x480 at 60Hz; 720x400 at 70Hz; 800x500 at 60Hz; 800x600 at 56, 60Hz; 1024x768 at 60Hz; 1280x800 at 60Hz; 1280x1024 at 60Hz; 1366x768 at 60Hz, 60Hz RB; 1440x900 at 60Hz, 60Hz RB; 1680x1050 at 60Hz, 60Hz RB  |
| Number of Colors            | 16.7 million   |
| Number of Touches           | Single-touch, Dual-touch and 10-touch  |
| Brightness (typical)        | LCD Panel: 250 nits; IntelliTouch: 225 nits; IntelliTouch Dual-Touch: 225 nits; TouchPro PCAP: 225 nits  |
| Response (typical)          | 14 msec  |
| Viewing Angle               | Horizontal: 89°/178°; Vertical: 89°/178°   |
| Contrast Ratio              | 1000:1   |
| On-Screen Display           | Accessible through switches on the unit's tethered OSD Control box.<br>Controls: Menu, Up, Down, Select, Power<br>Settings: Brightness, Contrast, Clock, Phase, H-position, V-position, Auto-Adjust, Aspect Ratio, Sharpness, Color, Temperature, OSD Timeout, OSD Language, OSD H-Position, OSD V-Position, Recall Defaults, Video Priority, Information, Touch On Sleep Mode, Touch Through<br>Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese<br>Lockouts: OSD, Power |
| Video                       | HDMI V1.3 Type A receptacle for HDMI input<br>Analog VGA on Female DB-15 connector<br>DisplayPort V1.1a - Supports later versions of Display Port video input<br><br>Input Video Horizontal Sync frequency range: 30 - 82KHz<br>Input Video Vertical Sync (frame rate) frequency range: 50-75Hz  |
| Power                       | External DC - Optional power brick (sold separately)<br>Monitor input power connector: Coaxial power jack (2.0mm (+0.0 -0.1mm) pin outer diameter, 6.4mm (+/- 0.3mm) barrel inner diameter, 8.8mm (+/- 0.3mm) barrel depth)<br>Monitor input power signal specifications: 12VDC +/- 5%   |
| Power Consumption           | ON (monitor + power brick): 25W<br>SLEEP (monitor + power brick): 1.5W<br>OFF (monitor + power brick): 0.5W  |
| Temperature                 | Operating: 0 °C to 40 °C (32 °F to 104 °F); Storage: -20 °C to 60 °C (-4 °F to 140 °F)   |
| Humidity                    | Operating: 20% to 80%; Storage: 10% to 95%   |
| Weight                      | Unpackaged: 11.24 lbs / 5.1 kg; Packaged: 18.08 lbs / 8.2 kg   |
| Shipping Dimensions         | 24.41" x 16.65" x 7.48" / 620mm x 423mm x 190mm  |
| Mounting Options            | VESA 4-hole 100mm mounting interface on rear of unit; 2-hole mounting interface on all 4 sides; Front mount with optional bezel kit (IntelliTouch/ IntelliTouch Dual-touch Models); Rack mount with optional kit (IntelliTouch/IntelliTouch Dual-touch Models); Flush mount with included brackets (TouchPro PCAP Models)  |
| Warranty                    | 3 years standard   |
| MTBF                        | 50,000 hours demonstrated  |
| Agency Approvals            | UL, FCC; RCM; cUL, IC; CCC; CE, TUV; VCCI; KCC; CoC; BSMI; CB; RoHS, China RoHS, WEEE, IMERC   |
| What's in the Box           | HDMI Cable, VGA Cable, OSD Remote, Touch USB Cable, User Manual CD and Quick Install Guide; For Zero-Bezel Models: Flush Mount Brackets w/Screws; For Bezeled Models: "L" (Side Mount) Brackets w/Screws, EEI Label, Japan Class-B TM info sheet   |

### Ordering Information

| Model | Part Number | Part Description           | Technology              | Interface       | Surface Treatment | Video Interface          | Availability |
|-------|-------------|----------------------------|-------------------------|-----------------|-------------------|--------------------------|--------------|
| 2294L | E330620     | ET2294L-2UWB-0-MT-ZB-NPB-G | TouchPro PCAP           | USB             | Clear             | HDMI, VGA & Display Port | Worldwide    |
|       | E327528     | ET2294L-8UWB-0-DT-NPB-G    | IntelliTouch Dual Touch | USB             | Clear             | HDMI, VGA & Display Port | Worldwide    |
|       | E327914     | ET2294L-8CWB-0-ST-NPB-G    | IntelliTouch            | Dual serial/USB | Clear             | HDMI, VGA & Display Port | Worldwide    |

### Extended Warranty Options

| Part Number | Description  |
|-------------|--|
| 758588-000  | 1 Year Extended Warranty, 7-inch to 22-inch LCD Touchmonitor |
| 930057-000  | 2 Year Extended Warranty, 7-inch to 22-inch LCD Touchmonitor |
| E67295-000  | Elo advance unit replacement for touchmonitors               |

**ITALY**  
TOUCH ITALIA SRL  
via Cavalla, 89  
20822 SEVESO MB

**Tel +39 0362 342387**  
**Fax +39 0362 344707**  
**mail: info@touchitalia.it**  
**www.touchitalia.it**

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo, IntelliTouch and TouchPro are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners. © 2017 Elo Touch Solutions, Inc. All rights reserved. 17034AES00033

