



55" HIGH BRIGHTNESS 3500 NIT FANLESS LCD WITH NARROW BEZEL MODEL DS552LT4-1

The DS552LT4-1 is a 55 inch ultra high brightness professional LCD with IPS technology. With a brightness rating of 3500 nits, this display features an LED back light for incredible, high contrast picture quality and low power consumption. The DS552LT4-1 features a 21.8 mm bezel-to-bezel width, perfect for video wall applications in bright environments. The display features an integrated Android™ based media player with WiFi offering users a complete media platform, allowing playback of local files and USB/SD card media.

Screen image simulated.
Android is a trademark of Google Inc.
The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License.

Key Features

- 3500 nits Brightness
- Fanless Thermal Management
- Integrated Android Media Player
- LED Backlit
- Blackening Defect Free in Direct Sunlight
- Fanless Thermal Management
- 1920 x1080 Full HD Native Resolution
- 10.9 mm Bezel Width

55" HIGH BRIGHTNESS 3500 NIT FANLESS LCD WITH NARROW BEZEL MODEL DS552LT4-1

PANEL

| | |
|---------------------------|----------------------|
| LCD Panel Type | 54.64 inches IPS LCD |
| Native Resolution | 1920 x 1080 |
| Backlight | LED |
| Brightness | 3500 nit |
| Default Color Temperature | D65 (6500 K) |
| Contrast Ratio | 3,000:1 |
| Color Depth | 8 bits |
| Response Time | 9 ms (typ) |
| Viewing Angle | 178° / 178° |
| Light Life Time | 50,000 hrs (typ.) |
| Blackening Defect Free | Up to 110°C (230°F) |
| Panel Surface | AR , 2H |

POWER

| | |
|-------------------|------------------------------|
| Power Supply | Internal |
| Rated Voltage | 100 V ~ 240 V, 50 Hz / 60 Hz |
| Power On Mode | 160 W (typ), 240 W (max) |
| Power Saving Mode | < 1 W |

MECHANICAL SPECS

| | |
|------------------------------|----------------------|
| Bezel Width (T/B/L/R) | Even bezel 10.9 mm |
| Cabinet Color | Black |
| Dimension (LxHxD, w/o stand) | 1240 x 710 x 87.7 mm |
| Weight (set/package) | 27.5kg / 32.5kg |
| VESA Mounting (dimension) | 400 x 400 mm |
| Orientation | Portrait / Landscape |

USER INTERFACE

| | |
|------------------------------|----------------------|
| Language | English |
| Daisy Chain | DVI, RS-232 |
| Proof of Image Retention | Yes |
| Dimming Control (DCR) | Yes |
| Built-in Video Wall Support | Up to 15x15 |
| ID Setting for Daisy Chain | Yes |
| On/Off Scheduling | Yes |
| Ambient Light Sensor | Yes |
| Total Turn-on time | Yes |
| Internal Temperature Sensor | Yes |
| Network Control | RS-232(IN/Out), RJ45 |
| OSD Menu Rotation | Yes |
| Carrying Handles | Yes |
| Fanless desing | Yes |
| Polarized sunglasses support | Yes |

I/O PORTS

| | |
|--------------|-----------------------------|
| DVI-D | In (x1), Out (x1) |
| Display Port | In (x1) |
| HDMI | In (x1) |
| RS-232 | In (x1), Out (x1) |
| RJ-45 | In (x1) |
| Audio | In (x1), Out (x1) |
| USB | USB2.0 for Internal Player* |
| SD Card Slot | For Internal Player* |

ACCESSORIES

| | |
|----------------------|--|
| Included Accessories | Power Cord, Remote controller, ESK302, QSG |
|----------------------|--|

ENVIRONMENT

| | |
|-----------------------|-----------------------------|
| Operating Temperature | 0° C ~ 45° C |
| Storage Temperature | -20° C ~ 60° C |
| Humidity | 10% ~ 80% RH Non-condensing |

CERTIFICATION

CE / FCC ClassB / ROHS

INTERNAL PLAYER

| | |
|-----------------------|--|
| Processor | ARM Cortex-A9 1.6 GHz, Quad-Core CPU |
| On chip cache memory | L2: 512KB |
| Clock speed | 1.6GHz |
| Main memory interface | 1GB DDR3/3L (1600MHz) |
| Graphics | 600M ARM Mali400MP4,2D/3D graphic engine, support OpenGL ES1.1/2.0, Open VG1.1 |
| Storage (FDM) | 8GB NAND Flash(2GB occupied by o/s, 6GB available depending on |
| Multimedia | H.264 encoder/decoder, MPEG-1/2/4, H.263, H.264 MVC, AVS, VC-1, VP8/6, RV |
| IO ports | USB 2.0, SD slot |
| Operating system | Yes |

