



DK SERIES

DK751DH5


75" 4000 nits 4K UHD Outdoor Ultra-High Brightness Hybrid Kiosk with Light Box



HYBRID
DIGITAL & STATIC



VANDAL
RESISTANT



SUNLIGHT
VIEWABLE IMAGE



SMART
LIGHT BOX



WEATHER
PROOF

FOR MORE INFORMATION

For more information about DynaScan, visit our website at www.dynascandisplay.com. Copyright © DynaScan Technology Inc. All rights reserved. All specifications and descriptions are subject to change without notice. Reproduction without permission is prohibited.

DynaScan

SPECIFICATION

MODEL	DK751DH5	
DISPLAY	LCD Panel Size	74.52"
	Native Resolution	3840 x 2160
	Brightness (w/o glass)	4,000 nits
	Color Depth	10 bits
	Contrast Ratio	3000 : 1
	Response Time (Typ.)	8 ms
	Viewing Angle	178° / 178°
	Light Lifetime (Typ.)	100,000 hrs
	Blackening Defect Free	Up to 110°C (230°F)
	Polarized Sunglasses Support	Yes
LIGHT BOX	Bezel Width (T/B/L/R)	89 / 89 / 89 / 89 mm
	Poster Size (WxH)	1200 x 1800 mm
	Kiosk Visual Opening (WxH)	1160 x 1710 mm
	Digital Side Bezel Width (T/B/L/R)	117.6 / 117.6 / 203.5 / 203.5 mm
MECHANICAL SPECS	Cabinet Color	Black
	Dimension (WxHxD, w/o stand)	1338.0 x 1962.0 x 254.0 mm
	Weight	< 350 kg [TBD] (lightbox excluded)
POWER	Orientation	Portrait
	Glass	Yes
	Air Vent	Yes
	Key Lock (Option)	Yes
	Power Supply	Internal
FEATURE	Rated Voltage	100-240V ~ 50/60HZ
	Power On Mode (Typ./ Max)	600 W / 1200 W [Basic]
	Language	English
	Support SNMP (Up to V3.0)	Yes
INPUT	Dimming Control	Yes
	Image Retention Protection	Yes
	Ambient Light Sensor	Yes
	Power On/Off Scheduling	Yes
	Internal Temperature Sensor	Yes
EXTERNAL CONTROL	HDMI	x3 (2160p)
	Display Port	x1
	USB 3.0	x1
	Micro SD Slot	x1
ENVIRONMENT	RS-232	In x1
	RJ-45	x2 (LAN)
CERTIFICATION	Operating Temperature	-30°~50° C
	Humidity	10% ~ 100% RH Non-condensing
	Water and Dust resistant design	IP56

DIMENSIONS

Unit: mm [inch]

